



## Diesel Fuel – Technical Specifications

### Overview

Senergy Holdings supplies premium-grade diesel fuel that meets international standards including EN590 and ASTM D975. Our diesel is ultra-low sulfur, ensuring cleaner combustion, reduced emissions, and improved engine performance.

### Diesel Specifications

Property	Specification
Standard	EN590 / ASTM D975
Sulfur Content	<10 ppm
Density @ 15°C	820–845 kg/m³
Cetane Number	≥ 51
Flash Point	>55 °C
Viscosity @ 40°C	2.0 – 4.5 cSt
Carbon Residue	<0.3 wt%
Water Content	<200 mg/kg

### Applications

- Automotive diesel engines (light-duty and heavy-duty vehicles)
- Industrial machinery and equipment
- Marine and power generation engines
- Agricultural equipment and off-road applications

### Quality Assurance

Our diesel undergoes rigorous testing in ISO-certified laboratories to ensure compliance with international standards. Each shipment is fully traceable and delivered with certificates of quality assurance.

### Contact Information

**Senergy holding company kpsc**

**Po box 9920| ahmadi 61010| kuwait**

**East ahmadi| block 8| plot 42| mezzanine**

**| Email: [info@senergy.com](mailto:info@senergy.com)**